EB-PU2216B

The EB-PU2216B is a high lumens 3LCD projector that's ultralightweight and compact.

The EB-PU2216B offers users significant advantages including much reduced size and weight, easier installation and set-up, simplified maintenance and great image quality. This ultra-lightweight, compact laser projector has been designed for use in large auditoriums, live events, concerts, conference rooms where it delivers high-impact immersive experiences.

Compact and lightweight

The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.

Flexibility

The EB-PU2216B's functionality enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

Reliability

Includes improved dustproofing as the hermetically sealed optical engine, and laser light source unit, prevent dust contamination to ensure enhanced durability.

DATASHEET / BROCHURE



KEY FEATURES

- Ultra-lightweight and compact Easy to store, transport and install
- Stunning image displays 16,000lm, 4K Enhancement technology, WUXGA resolution
- Easy to use Simple installation, stacking, lens flexibility and control
- Fit-and-forget reliability Enhanced dustproof construction. IP5x certified
- Environmental benefits Lower power consumption, reduced packaging, reduced weight





PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology	
LCD Panel	1,03 inch with C2 Fine	
MAGE		
Color Light Output	16.000 Lumen- 11.200 Lumen (economy) In accordance with IDMS15.4	
White Light Output	16.000 Lumen - 11.200 Lumen (economy) In accordance with ISO 21118:2020	
Resolution	WUXGA	
High Definition	4K enhancement	
Aspect Ratio	16:10	
Contrast Ratio	Over 2.500.000 : 1	
Native Contrast	2.000 : 1	
Light source	Laser	
Laser Light source	20.000 hours Durability High, 30.000 hours Durability Eco	
Colour Video Processing	10 Bits	
Colour Reproduction	Upto 1.07 billion colours	
HDR support	HDR10, HLG	
OPTICAL		
Throw Ratio	0,35 - 7,41:1	
Zoom	Motorized, Factor: 1 - 1,6	
Lens	varies by lens	
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %, varies by lens	
Lens position memory	10 positions	
Screen Size	60 inches - 1.000 inches, varies by lens	
Projection Distance Wide)varies by lens	
Projection Distance Tele)varies by lens	
Projection Lens F Number	varies by lens	
Projection Lens Focal Length	-	
Projection Lens Focus	Motorized	
Interchangeable Lens	Yes	
Standard Lens	Not included	
Mechanical shutter	Yes	
CONNECTIVITY		
Interfaces	USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet Interface (1000 Base-T/ 100	
	Base TX/ 10-Base-T), VGA in, DVI in, HDMI in, HDBaseT, Jack plug out, 3G-SDI Input, 3G-SDI	
	Output, Wireless LAN IEEE 802.11a/b/g/n (optional), Near Field Communication (NFC), USB	
Natural Dratasal	content playback, Remote	
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink	
ADVANCED FEATURES		
Security	${\it Kensington \ lock, Security \ bar, Password \ lock, Wireless \ LAN \ unit \ lock, Wireless \ LAN \ security,}$	
	Password protection	
Other features	21:9 aspect ratio support, 4K enhancement, Auto Power On, Auto source search, Direct Power	
	on/off, Edge Blending, Lens position memory, Long light source life, OSD copy function, Point	
	$\mbox{correction, Power on button, Quick Corner, Schedule Function, Split-Screen-Function, Super}$	
	and the Web Control Web Devices During the Ann	
	resolution, Web Control, Web Remote, iProjection App	
Video Color Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709	
Video Color Modes Projector control		
	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709	

EB-PU2216B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document





PRODUCT SPECIFICATIONS

Warranty	36 months Carry in Optional warranty extension available	
OTHER	20 martha Carrain	
Colour	Black	
Positioning	Ceiling Mounted, Desktop, Flying Frame	
Options	Camera module, Ceiling mount, Wireless LAN unit	
Included Software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Config Tool, Epson Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool	
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%	
Supported Temperature	Storage -10° C - 60° C	
Noise Level	Normal: 38 dB (A) - Economy: 34 dB (A)	
Product weight	24,2 kg	
Product dimensions	586 x 492 x 218 mm (Width x Depth x Height)	
Supply Voltage	AC 200 V - 240 V, 50 Hz - 60 Hz	
Heat Dissipation	3.682 BTU/hour (max)	
	in JBMS-84 902 Watt	
Power consumption	1.083 Watt, 773 Watt (economy), 0,4 Watt (standby), On mode power consumption as defined	
GENERAL		

EB-PU2216B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document



OPTIONAL ACCESSORIES

- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Camera Unit ELPEC01 V12HA46010
- Ceiling Mount ELPMB68
- V12H006AE0
- Extension Pole ELPMB70 For ELPMB68 V12H006AG0
- Truss Adaptor ELPMB71 For ELPMB68 V12H006AH0
- Stacking Frame ELPMB59 EB-PU2200 Series (EVO) V12H996B59

OPTIONAL LENSES

- Lens ELPLL08 Long throw EB-PU Series V12H004L08
- Lens ELPLM10 Mid throw 3 EB-PU Series V12H004M0A
- Lens ELPLM11 Mid throw 4 EB-PU Series V12H004M0B
- Lens ELPLM15 Mid throw EB-PU Series V12H004M0F
- Lens ELPLU03S Short throw off axis 1 EB-PU Series V12H004UA3
- Lens ELPLU04 Short throw off axis 2 EB-PU Series V12H004U04
- Lens ELPLW06 Wide zoom 2 EB-PU Series V12H004W06
- Lens ELPLW08 Wide throw EB-PU2000 Series V12H004W08
- Lens ELPLX02S UST EB-PU2000 Series V12H004X0B
- Lens ELPLX02WS UST EB-PU2000 Series V12H004Y0B

LOGISTICS INFORMATION

ѕки	V11HA67840
EAN code	8715946703237
Country of Origin	China
Layer	1 Units



Epson Ibérica, S.A.U. Tel.: 93 582 15 00 Tel.: 902 49 59 69 (Preventa) Fax: 93 582 15 55 www.epson.es Central: Sant Cugat Camí de Ca n'Ametller, 22 Edificio 2 08195 Sant Cugat del Vallès (Barcelona)

Las marcas comerciales o marcas registradas son propiedad de Seiko Epson Corporation o de sus respectivos propietarios. La información sobre los productos puede estar sujeta a modificación en función de las actualizaciones en sus especificaciones.

EB-PU2216B

